



Couplings Size/type	Torque Nm	Max Speed	Max Bore (part)			Dimensions (mm)										Weight		
			1,5	4	2	$\phi A$	$\phi B$	$\phi C$	$\phi E$	D1	D2	G	K	T	S	B	A	H
68 B	34	5000	24	28	-	68	46	-	-	20	-	8	-	-	-	0,6		
80 B,H	60	5000	30*	38	-	80	68	55	-	30	45	10	-	-	100	1,5		3,9
															140			2,9
95 B,H	100	5000	42	42	-	95	76	70	-	35	45	12	-	-	100	2,6		3,9
															140			4,2
110 A,B,H	160	5000	48	48	38	110	86	80	62	40	50	14	20	33	100	3,9	3,5	5,8
															140			6,2
															180			6,6
125 A,B,H	240	5000	55	55	45	125	100	90	75	50	50	18	23	38	100	6,2	5,6	8,2
															140			8,7
															180			9,2
															200			9,5
															250			10,0
																		11,3
																		140
140 A,B,H	360	4900	60	60	50	140	100	100	82	55	65	20	28	43	180	6,9	7,0	12,3
															200			12,6
															250			13,2
160 A,B,H	560	4250	65	65	58	160	108	108	95	60	70	20	28	47	100	9,4	9,8	14,5
															140			15,2
															180			16,0
															200			16,4
															250			17,4
180 A,B,H	880	3800	75	75	65	180	125	125	108	70	80	20	30	50	140	14,0	14,2	21,0
															180			21,9
															200			22,4
															250			23,4
200 A,B,H	1340	3400	85	85	75	200	140	140	122	80	90	24	32	53	140	20,0	19,8	29,2
															180			30,3
															200			30,9
															250			32,1
225 A,B,H	2000	3000	90	90	85	225	150	150	138	90	100	18	38	61	140	24,5	27,0	38,2
															180			39,0
															200			39,7
															250			41,5
250 A,B,H	2800	2750	100	100	95	250	165	165	155	100	110	18	42	69	180	34,0	37,0	53,5
															200			54,7
															250			56,5
280 A,B	3900	2450	110	105	105	280	180	-	172	110	-	42	42	73	45,0	48,0		
315 A	5500	2150	100	100	100	315	165	-	165	125	-	-	47	78		63,0		
350 A	7700	1950	110	110	110	350	180	-	180	140	-	-	51	83		86,0		
400 A	10300	1700	120	120	120	400	200	-	200	160	-	-	56	88		122,0		
440 A	13500	1550	130	130	130	440	215	-	215	180	-	-	64	99		159,0		
480 A	16600	1400	145	145	145	480	215	-	215	190	-	-	65	104		200,0		

S1; 2 - 4 mm for size 68 to 140, 2 - 6 mm size 160 to 225 and 3 - 8 mm for 250 to 400