









POLYURETHAN szállítóhevederek

1 , 2 , vagy 3 betétes polyester szálerősítéssel

Típus	FDA 2005/79 /CE	A N T I S T A T	Szállító oldali szín	Vastag- ság [mm]	Súly [kg/m 2]	Min. görgő átmérő (1)	Min. hőmér- séklet [°C]	Max hőmér- séklet [°C]	Max szélesség [mm]
									
EL2-U10 FL	x	x	Zöld	1,0	1,2	10	-20	60	2000
EL2-U10 W	x		Fehér	1,0	1,0	10	-20	60	2000
EL2-U10 HP W	x		Fehér	1,0	1,1	10	-30	60	2000
EL2-U10 HP blue	x		Kék	1,0	1,1	10	-30	60	2000
EL3-U15 FL	x	x	Zöld	1,5	1,6	10	-20	60	2000
EL4-U20 W	x		Fehér	2,0	2,2	10	-20	60	2000
EL4-U20 FH	x		zöld	2,1	2,1	10	-20	60	2000
1M5 U0-U2 W A	x	x	Fehér	0,7	0,8		-20	100	2000
1M5 U0-U2 W A LF VL	x	x	Fehér	0,7	0,8		-20	100	1500
1M5 U0-U2 D W A	x	x	Fehér	0,7	0,7		-30	100	2000
1M5 U0-U2 HP W A	x	x	Fehér	0,7	0,8		-30	110	2000
1M5 U0-U2 HP W S A	x	x	Fehér	0,7	0,8		-30	110	2000
1M5 U0-U2 HP VL blue A	x	x	Kék	0,7	0,8		-30	110	2000
1M5 U0-U2 PN yellow	x		Sárga	1,1	0,9		-20	100	2000
1M6 U0-U2	x	x	Zöld	0,8	0,9		-20	100	2000
1T6 U0-U2 HP W A	x	x	Fehér	0,8	0,8		-30	110	2000
1M6 U0-U5 FL	x	x	Zöld	1,0	1,0	10	-20	100	2000
1M6 U3-U3 FL	x	x	Zöld	1,2	1,3	10	-20	100	2000
1M6 U5-U5 FL	x	x	Zöld	1,6	1,9	20	-20	100	2000
1M12 U0-U3 HP PN N S		x	Fekete	1,5	1,6		-30	110	2000
ST06	x	x	Zöld	0,6	0,6	10	-30	100	2000
2M5 U0-U0 HP A	x	x	Fehér	1,0	1,0		-30	110	2000
2M5 U0-U2 A	x	x	Zöld	1,2	1,4		-20	100	2000
2M5 U0-U2 W A	x	x	Fehér	1,3	1,5		-20	100	2000
2M5 U0-U2 LF W	x	x	Fehér	1,3	1,5		-20	100	2000
2M5 U0-U2 HP W S A	x	x	Fehér	1,3	1,4		-30	110	2000
2M5 U0-U2 HP W A	x	x	Fehér	1,3	1,4		-30	110	2000
2M5 U0-U2 HP PN W A	x	x	Fehér	1,4	1,4		-30	110	2000
2M5 U0-U2 HP VL blue A	x	x	Kék	1,3	1,4		-30	110	2000
2M5 U0-U2 HP PN blue A	x	x	Kék	1,6	1,5		-30	110	2000
2M5 U2-U2 HP VL blue A	x	x	Kék	1,5	1,7	10	-30	110	2000

2MT6 U0-0	x		Nyers	1,5	1,4		-20	100	2000
2M8 U0-U0	x	x	Nyers	1,3	1,4		-20	100	2000
2M8 U0-U0 SP	x	x	Nyers	1,3	1,0		-20	100	3000
2M8 U0-U0 GR		x	Szürke	1,3	1,4		-20	100	2000
2M8 U0-U0 GR SP		x	Szürke	1,3	1,4		-20	100	3000
2T8 U0-0	x		Fehér	1,3	1,4		-20	100	3000
2M8 U0-U2		x	Zöld	1,4	1,6		-20	100	2000
2M8 U0-U2 N HC		x	Fekete	1,6	1,6		-20	100	2000
2M8 U0-U2 SP		x	Zöld	1,5	1,6		-20	100	3500
2M8 U0-U2 W A SP	x	x	Fehér	1,5	1,5		-20	100	3500
2M8 U0-U2 N SP		x	Fekete	1,4	1,4		-20	100	3500
2M8 U0-U5 TR	x	x	Áttetsző	1,7	2,0	40	-20	100	2000
2T12 U0-U2 W SP	x	x	Fehér	1,6	1,8	30	-20	100	3000
2T12 U0-U2 HP VL W A	x	x	Fehér	1,6	1,7		-30	110	2000
2T12 U0-U2 FM FR		x	Antracit	1,8	1,8	30	-20	100	2000
2M12 U0-U3 R A	x	x	Zöld	1,7	1,8	40	-20	100	2000
2M12 U0-U3 R W A	x	x	Fehér	1,7	1,8	40	-20	100	2000
2M12 U0-U3 R N A		x	Fekete	1,7	1,8	40	-20	100	2000
2M12 U0-V-U5		x	Zöld	2,0	2,5	60	-10	60	2000
2M12 U0-V-U5 SP		x	Zöld	2,1	2,5	60	-10	60	3000
2M12 U0-U10 W A	x	x	Fehér	2,4	2,7	50	-20	100	2000
2M12 V5-V-U10 W	x	x	Fehér	3,5	4,0	80	-10	60	2000
2M12 U0-U15 LT W	x		Fehér	6,0	3,5	50	-20	100	600
2M12 U0-U20	x	x	Zöld	3,4	3,8	80	-20	100	2000
3M8 U0-U3		x	Zöld	2,2	2,4	60	-20	100	2000
3M8 U0-V-U3 N SP		x	Fekete	2,1	2,6	60	-10	60	3000
3M18 U0-V-U10		x	Zöld	3,7	4,4	100	-10	60	2000
3M18 U0-V-U10 SP		x	Zöld	3,7	4,4	100	-10	60	3000

PVC szállítóhevederek










1 , 2 , vagy 3 betétes polyester szálerősítéssel

Típus	FDA 2005/79 /CE	A N T I S T A T	Szállító oldali szín	Vastag- ság [mm]	Súly [kg/m 2]	Min. görgő átmérő (1)	Min. hőmér- séglet [°C]	Max hőmér- séglet [°C]	Max. Szélesség [mm]
1M6 U0-V3 A N	x		Fekete	0,8	0,8	20	-10	60	3500
1M6 U0-V5	x		Zöld	1,0	1,1	20	-10	60	3000










1M6 U0-V5 W	x	x	Fehér	1,0	1,1	20	-10	60	3000
1M6 U0-V5 N		x	Fekete	1,0	1,1	20	-10	60	3000
1M6 U0-V5 FM N		x	Fekete	1,1	1,0	30	-10	60	3000
1M6 U0-V5 SM N		x	Fekete	1,0	1,1	20	-10	60	2000
1M6 V5-V5		x	Zöld	1,8	2,0	30	-10	60	3000
1M12 U0-V5 N		x	Fekete	1,8	2,0	30	-10	60	2000
1M12 U0-V5 FH N		x	Fekete	2,0	2,1	30	-10	60	2000
1M12 U0-V5 SM N		x	Fekete	2,1	2,0	30	-10	60	2000
2T5 0-V-0	x	x	Fehér	1,6	1,7	20	-10	60	2000
2MT5 U0-V3 N		x	Fekete	1,8	2,0	20	-10	60	3000
2MT5 U0-V3 FH N		x	Fekete	2,1	1,9	30	-10	60	2000
2MT5 U0-V3 SM N		x	Fekete	1,9	2,0	20	-10	60	2000
2M8 U0-V-U0	x	x	Nyers	1,5	1,5	30	-10	60	3000
2T8 U0-V-0	x		Nyers	1,4	1,4	30	-10	60	3000
2M8 U0-V5 A		x	Zöld	2,0	2,3	30	-10	60	3500
2M8 U0-V5 W	x		Fehér	2,0	2,3	30	-10	60	3000
2M8 U0-V5 PN W	x		Fehér	2,2	2,3	30	-10	60	2000
2M8 U0-V5 blue	x		Kék	2,0	2,3	30	-10	60	3000
2M8 U0-V5 FM		x	Zöld	2,1	2,3	30	-10	60	3000
2M8 U0-V5 FM N		x	Fekete	2,1	2,3	30	-10	60	3000
2M8 U0-V5 PS GR		x	Szürke	2,3	2,3	30	-10	60	500
2M8 U0-V5 RT GR		x	Szürke	2,2	2,3	30	-10	60	2000
2M8 V5-V5 W	x		Fehér	2,5	3,0	50	-10	60	2000
2M8 V5-V5 blue	x		Kék	2,5	3,0	50	-10	60	2000
2M8 U0-V17 GP		x	Zöld	5,2	3,7	50	-10	60	2000
2M10 U0-V10			Zöld	2,8	3,3	50	-10	60	3000
2M10 U0-V10 W	x		Fehér	2,8	3,3	50	-10	60	3000
2M10 U0-V10 blue	x		Kék	2,8	3,1	50	-10	60	3000
2M12 U0-V-U0 GR		x	Szürke	1,7	1,6	40	-10	60	3000
2T12 U0-V0			Zöld	2,5	2,6	80	-10	60	2000
2M12 U0-V3		x	Zöld	1,9	2,1	40	-10	60	3000
2M12 U0-V3 N		x	Fekete	1,9	2,1	40	-10	60	3000
2MT12 X0-V6 FH N		x	Fekete	2,1	2,0	60	-10	60	2000
2M12 U0-V7 LG		x	Zöld	2,4	2,4	40	-10	60	2000
2M12 U0-V8 RT		x	Zöld	2,3	2,4	40	-10	60	2000
2M12 U0-V10 A		x	Zöld	2,5	2,9	50	-10	60	3500
2M12 U0-V10 W	x		Fehér	2,5	2,9	50	-10	60	3000
2M12 U0-V10 N		x	Fekete	2,9	3,5	60	-10	60	3000
2M12 U0-V10 RT		x	Zöld	2,6	2,6	50	-10	60	2000
2T12 U0-V10		x	Zöld	2,5	2,9	50	-10	60	3000
2T12 U0-V10 W	x		Fehér	2,5	2,9	50	-10	60	3000
2M12 V5-V10			Zöld	3,0	3,5	80	-10	60	2000
2M12 V5-V10 W	x		Fehér	3,1	2,8	80	-10	60	2000

2T12 V5-V10 W	x		Fehér	3,0	3,5	80	-10	60	2000
2T12 V5-V10 blue	x		Kék	3,1	3,5	80	-10	60	2000
2M12 U0-V15 W	x		Fehér	3,0	3,4	80	-10	60	3000
2M12 U0-V15 CL W	x		Fehér	5,5	3,5	80	-10	60	2000
2M12 U0-V15 FB W	x		Fehér	4,1	3,5	80	-10	60	2000
2M12 U0-V15 GPL N		x	Fekete	3,8	3,5	60	-10	60	2000
2M12 U0-V15 ST W	x		Fehér	3,6	3,5	80	-10	60	2000
2M12 U0-V20 GP		x	Zöld	5,5	3,9	50	-10	60	2000
2T12 U0-V20 GP W	x		Fehér	5,5	3,9	50	-10	60	2000
2T20 V10-V10 W A	x	x	Fehér	4,5	5,4	120	-10	60	2000
2M20 U0-V25 RT			Zöld	5,0	5,7	100	-10	60	2000
3T18 U0-V0			Zöld	3,7	3,9	120	-10	60	2000
3M18 U0-V15 A		x	Zöld	4,2	4,9	100	-10	60	3000
3M18 U0-V15 W	x		Fehér	4,2	4,9	100	-10	60	3000
3T18 U0-V15		x	Zöld	4,2	4,9	100	-10	60	3000
3T18 U0-V15 W	x		Fehér	4,2	5,0	100	-10	60	3000
3T18 V10-V20 W	x	x	Fehér	6,7	7,9	100	-10	60	2000
3T30-V10-V10 W	x	x	Fehér	6,3	7,4	200	-10	60	2000
3M30 U0-V25 RT			Zöld	6,6	7,8	200	-10	60	2000
1M12 U0-V5 PN FR		x	antracit	1,8	1,9	40	-10	60	2000
2M5 U0-V5 PN FR		x	antracit	1,9	2,1	40	-10	60	2000
2M12 U0-V-U0 FR		x	antracit	2,5	2,5	40	-10	60	2000
2M12 U0-V7 LG FR		x	antracit	2,7	2,4	40	-10	60	2000
2M12 U0-V10 FR		x	antracit	2,5	2,9	50	-10	60	3000
2M12 U0-V10 RT FR		x	antracit	2,7	2,9	60	-10	60	2000
2T12 U0-V10 FM FR		x	antracit	2,6	2,9	50	-10	60	3000
2M12 U0-V20 FB FR		x	antracit	4,6	3,9	50	-10	60	2000
2M12 U0-V20 GP FR		x	antracit	5,5	3,9	50	-10	60	2000
2M12 U0-V30 RL FR		x	antracit	8,5	5,8	60	-25	70	1200
2M8 U0-V5 AGR			Zöld	2,0	2,2	30	-15	60	3000
2M12 U0-V10 AGR			Zöld	2,5	2,9	50	-15	60	3000
2M12 V5-V10 AGR			Zöld	3,1	3,6	80	-15	60	2000
2M12 V5-V10 AGR N			Fekete	3,0	3,4	80	-15	60	2000
2T12 V5-V10 AGR			Zöld	3,1	3,6	80	-15	60	2000
2T12 V10-V12 AGR			Zöld	4,0	4,6	80	-15	60	2000
3M15 U0-V15 AGR			Zöld	4,1	4,6	100	-15	60	3000
3M15 V5-V10 AGR			Zöld	4,1	4,8	100	-15	60	2000










Elstomer szállítóhevederek

Típus	FDA 2005/79 /CE	A N T I S T A T	Szállító oldali szín	Vastag- ság [mm]	Súly [kg/m 2]	Min. görgő átmérő (1)	Min. hőmér- séglet [°C]	Max. hőmér- séglet [°C]	Max. szélesség [mm]
									
2M8 U0-U-G5 FL	x		Zöld	2,0	2,4	25	-20	100	2000
2M8 U0-U-G10 FH	x		Zöld	2,3	2,4	50	-20	100	2000
2M8 U0-U-G15 FL	x		Zöld	3,0	3,4	50	-20	100	2000
2T12 U0-U-G10 FH	x		Zöld	2,2	2,2	50	-20	100	2000
2M12 U0-G25 GP	x		Zöld	5,5	4,5	60	-40	100	1200
2T12 U0-G25 GP	x		Zöld	5,5	4,5	80	-40	100	1200
2T12 U0-G35 GP	x		Zöld	6,5	6,5	80	-40	100	1200

Polyamid szállítóhevederek

Típus	FDA 2005/79 /CE	A N T I S T A T	Szállító oldali Szín	Vastag- ság [mm]	Súly [kg/m 2]	Min. görgő átmérő min. (1)	Min. hőmér- séglet [°C]	Max hőmér- séglet [°C]	Max. szélesség [mm]
									
2P6 G1-0	x		Fehér	1,8	1,8	20	-20	100	2000
PR0-L	x		Zöld	0,9	0,8	15	0	100	500
P1-L	x		Zöld	1,3	1,1	25	0	100	500
CNG	x		Zöld	0,7	0,7	20	-20	100	1200
CNPG	x		Zöld	1,0	0,9	20	0	100	500
N	x		Zöld	0,6	0,6	15	-20	100	1200
N8	x		Zöld	1,0	0,9	15	-20	100	1200
NT1	x		Zöld	1,2	1,2	15	-20	100	1200
NT2	x		Zöld	2,0	2,1	20	-20	100	1200
NT3	x		Zöld	3,0	3,2	40	-20	100	1200
NT4	x		Zöld	4,0	4,3	60	-20	100	

Silicon szállítóhevederek

Típus	FDA 2005/79 /CE	A N T I S T A T	Szállító Oldali szín	Vastag- ság [mm]	Súly [kg/m ²]	Min. görgő átmérő (1)	Min. hőmér- séklet [°C]	Max. hőmér- séklet [°C]	Max. szélesség [mm]
									
1M6 U0-S0	x	x	Áttetsző	0,6	0,4	20	-30	100	2000
2M8 U0-U-S0		x	Nyers	1,3	1,1	30	-20	100	2000
2M8 U0-U-S GR		x	Szürke	1,3	1,1		-20	100	2000
2MT8 S0-S0		x	Nyers	1,2	1,1	30	-40	160	2000
2MT8 S0-S2	x	x	Áttetsző	1,3	1,3	30	-40	160	2000
2T12 U0-U-S2	x	x	Áttetsző	1,4	1,3	30	-30	100	2000
2FG12 S0- S3WHITE			Fehér	1,1	1,5	40	-40	250	140